I'm not a robot

Nikon d7100 user manual

Highlight Select image and press 2. M (Y) button Sub-command dial Control panel... Camera level Camera tilted left or right... Option Description a DX (24×16) Pictures are recorded using a 23.5 × 15.6 mm image area (DX format). Press 2 to display options for the selected menu item. Copy the photograph. C The Shooting Menu: Shooting Options To display the shooting menu, press G and select the C (shooting menu) tab. If the built-in flash or other flash units are used, shutter speed is set 1/320 s s. Page 188 Non-CPU Lenses When using non-CPU lenses, be sure to enter the focal length and maximum aperture using the Non-CPU lens data option in the setup menu (0 149). Single-lens reflex digital camera Lens mount Nikon F mount (with AF coupling and AF contacts) Nikon DX format; focal length in 35 mm [135] format equivalent to Effective angle of view approx. 8 Hi 0 . Page 368 Battery One rechargeable Li-ion EN-EL15 battery Battery pack Optional MB-D15 multi-power battery pack with one rechargeable Nikon EN-EL15 Li-ion battery or six AA alkaline, Ni-MH, or lithium batteries EH-5b AC adapter; requires EP-5B power connector (available separately) AC adapter Tripod socket Tripod socket in. Page 3 Where to Find It Find what you're looking for from: The Table of Contents .... After choosing the desired setting, press J to exit. NIKON D7100 º '... A program selection dialog will be displayed;... 263 Flicker Reduction.....264 Time Zone and Date..... White balance is fine-tuned using the White balance option in the shooting menu or by pressing the L (U) button and rotating the sub-command dial. Note that noise reduction will be performed if the subject is poorly lit, increasing recording times. Press Selecting Press displays the following options: Option Description Preview... Long Time-Exposures (M Mode Only) Select the following shutter speeds for long time- exposures of moving lights, the stars, night scenery, or fireworks. K button See Also For information on choosing a language and setting the time and date, see page 28. Straighten G button N retouch menu Create a straightened copy of the selected image. Choosing Auto allows the camera to set ISO sensitivity automatically in response to lighting conditions. Focus can be adjusted automatically (see below) or manually (0 78). Image Dust Off Ref Photo G button B setup menu Acquire reference data for the Image Dust Off option in Capture NX 2 (available separately; for more information, see the Capture NX 2 manual). Page 175 Interval Timer Photography Interval timer photography can not be combined with remote control photography using the optional ML-L3 remote control (0 127), live view photography (0 153), or movie live view (0 161). Option Description Create a copy from which the opening or closing footage has been 9 Choose start/end point removed. Highlight Selective color in the retouch menu and press 2 to display a picture selection dialog. Zoom in on X (T) See page 195 for more information. Highlight the item you wish to move and press J. Turn the camera off. DX (24×16) Image Area Image quality Image size... Highlight items using the multi selector and press J to view options for the highlighted item. u Selective Color All colors other than the selected colors are recorded in black and white. The memory card access lamp will light for a few seconds. Manual Nikon D7100. 262 Monitor Brightness .....262 Image Dust Off Ref Photo..... The selected photograph is displayed with the selected crop shown in yellow; create a cropped copy as described in the following table. Page 172 Interrupting Multiple Exposures To interrupt a multiple exposure before the specified number of exposures have been taken, select Off for multiple exposure mode. The name of the menu will change from "MY MENU"... Page 338 • Communication Unit UT-1 (0 206): When connected to the camera using the USB cable supplied with the camera, the UT-1 can be used to connect to Ethernet networks and upload pictures to an ftp server or control the camera remotely using optional Camera Control Pro 2 software. Highlight Multiple exposure mode and press 2. Page 179 To recall lens data when using a non-CPU lens: Assign non-CPU lens number selection to a camera control. This license is not a sale of the Manual and you do not become the owner of the Manual through your purchase of any product, download and/or use. Page 150 Shutter Speeds Available with the Built-in Flash The following shutter speeds are available with the built-in flash. By clicking the "Download" button on this page in order to start downloading the Manual, you indicate your acceptance of this Agreement and are agreeing to be bound by the terms of this Agreement. Printing Pictures One at a Time Select a picture. To maximize shooting time, charge the battery in the supplied MH-25 battery charger before use. G button Choose a lens number. Press the a button to exit live view mode. Exposure Program (Mode P) The exposure program for mode P is shown in the following graph: ISO 100; lens with maximum aperture of f/1.4 and minimum aperture of f/16 (e.g., AF-S NIKKOR 50mm f/1.4G) Shutter speed (seconds) The maximum and minimum values for EV vary with ISO sensitivity; the above graph assumes an ISO sensitivity of ISO 100 equivalent. Preserving Detail in Highlights and Shadows Active D-Lighting (P, S, A, and M Modes Only) Active D-Lighting preserves details in highlights and shadows, creating photographs with natural contrast. Servicing the Camera and Accessories The camera is a precision device and requires regular servicing. • To take a series of multiple exposures, select 6 On (series). The histogram will be updated to show only the data for the portion of the image visible in the monitor. Select ADL bracketing. The dialog shown at right will be displayed. Press 4 or 2 to highlight number of intervals or number of shots; press 1 or 3 to change. Use of autumn leaves. Page 164 Exposure and Flash Bracketing In continuous low speed and continuous high speed release modes, shooting will pause after the number of shots specified in the bracketing program have been taken. Select Date: Deleting Photographs Taken on a Selected Date Choose Select date. Frame the photograph (0 37). To choose another special effect mode, rotate the main command dial. Deleting Photographs To delete the photograph displayed in full-frame playback or highlighted in the thumbnail list, press the O (Q) button. If card is damaged, This memory card contact retailer or Nikon- cannot be used. WR-1 Wireless Remote Controllers When a WR-1 is connected to the camera accessory terminal, the shutter can be released using another WR-1. The color temperature is displayed in the control panel. Use Only Nikon Flash Accessories Use only Nikon flash units. Multiple exposure shooting will continue until you select Off for Multiple exposure mode. w Autofocus mode The current autofocus mode. press P. P, S, A, and M Modes Select these modes for full control over camera settings. Fast shutter speed (Slow shutter speed (1600... Bracketing increment D button Sub-command dial Control panel The bracketing programs with an increment of EV are listed below: Control panel display No. Page 163 Frame a photograph, focus, and shoot. Choose the flash level (0 246). Display options. containing images. Nikon will not be held liable for damages that may result from any mistakes that this manual may contain. Keep these safety instructions where all those who use the product will read them. Displayed if shooting will end in 30 s or less. Time Zone and Date G button B setup menu Change time zones, set the camera clock, choose the date display order, and turn daylight saving time on or off (0 28). Page 156 Take the photograph. Use of a tripod is recommended. CLS-Compatible Flash Units The camera can be used with the following CLS-compatible flash units: •... L (U) button Sub-command dial Control panel Select direct measurement mode. 0.94× (50 mm f/1.4 lens at infinity, –1.0 m –1 Eyepoint 19.5 mm (–1.0 m ; from center surface of viewfinder eyepiece lens) –1 Diopter adjustment –2–+1 m... Page 27 Notice Concerning Prohibition of Copying or Reproduction Note that simply being in possession of material that has been digitally copied or reproduced by means of a scanner, digital camera, or other device may be punishable by law. Multiple Exposure (P, S, A, and M Modes Only) Follow the steps below to record a series of two or three exposures in a single photograph. When Auto is selected, ISO AUTO and the sensitivity chosen by the camera is displayed as shown at right. M: Manual In manual mode, you control both shutter speed and aperture. Side-by-side Comparison Compare retouched copies to the original photographs. The diameter (φ) of this circle can be set to 6, 8, 10, or 13 mm or to the average of the entire frame. Description W (S) Press W (S) to reduce the size of the crop. d6: Max. Position the item. Recording may end unexpectedly when cards with slower write speeds are used. 35 Flash mode.....120 Autofocus mode ..... Playback Display Options G button D playback menu Choose the information available in the playback photo information display (0 187). Hold the camera firmly when removing the rubber eyecup. Press the G button to display the menus, highlight the desired option and press 2. Battery Info G button B setup menu View information on the battery currently inserted in the camera. GENERAL This Agreement is governed by and shall be construed in accordance with the laws of Japan without regard to its conflicts of laws principles. Highlight Image 1 or Image 2 and optimize exposure for the overlay by pressing 1 or 3 to select gain from values between 0.1 and 2.0. Repeat for the second image. Page 372 Using the Built-in Flash When using the built-in flash, be sure the subject is at a range of at least 0.6 m (2 ft) and remove lens hoods to prevent vignetting (shadows created where the end of the lens obscures the built-in flash). Choose the flash control mode and output level for the built-in flash. Page 24 • When the battery is not in use, attach provided or sold by Nikon for the the terminal cover and store in a cool, purpose to maintain compliance with dry place. 177 % Night Vision.....178 g Color Sketch .....178 i Miniature Effect .....178 u Selective Color .....179 1 Silhouette .....179 2 High Key .....179 3 Low Key .....179 Options Available in Live View .....180 More on Playback Full-Frame Playback..... Option Description B AE/AF lock Focus and exposure lock while the MB-D15 A AE-L/AF-L button is pressed. G button The options in the retouch menu are used to create trimmed or retouched copies of existing pictures. To choose from a list of existing folders, choose Select folder from list, highlight a folder, and press J. Choose from values between –5 EV (underexposure) and +5 EV (overexposure) in increments of EV. Option Description Flash output is adjusted automatically in response to shooting 1 TTL conditions. To view the menus, press the G button. • Print select: Select pictures for printing. X (T) button Main command dial Control panel Choose an image size (0 68). Highlight Preset manual in the white balance menu and press 2. White balance increment D button... The effect is displayed in the monitor together with red, green, and blue histograms (0 189) giving the distribution of tones in the copy. Page 55 Attach the lens. To prevent Length of exposure: 35 s blur, use a tripod or an optional wireless remote Aperture: f/25 controller (0 309) or remote cord (0 310). Highlight Save settings and press J to assign the settings selected in Steps 1 and 2 to the mode dial position selected in Step 4. Choose from Overflow (the card in Slot 2 is used only when the card in Slot 1 is full), Backup (each picture is recorded twice, once to the card in Slot 1 and again to the card in Slot 2), and RAW Slot 1—JPEG Slot 2 (as for Backup, except that the NEF/ RAW copies of photos recorded at settings of NEF/RAW + JPEG are recorded only to... Page 149 Default Flash Modes Default flash modes are shown below. Page 176 Pausing Interval Timer Photography Interval timer photography can be paused by: • Pressing the J button between intervals • Highlighting Start > Pause in the interval timer menu and pressing J • Turning the camera off and then on again (if desired, the memory card can be replaced while the camera is off) •... 0.6–6.0 2 ft–19 ft 8 in. Page 53 If the problem persists, cease use immediately and take battery and charger to your retailer or a Nikon-authorized service representative. Getting to Know the Camera Take a few moments to familiarize yourself with camera controls and displays. You must reproduce on each copy the Nikon copyright notice and any other proprietary legends that were on the original. Select Choose non-CPU lens number as the "Press + command dials" option for a camera control in the Custom Settings menu. AF-mode button Sub-command dial Control panel Viewfinder 3D-tracking When the shutter-release button is pressed halfway, the colors in the area surrounding the focus point are stored in the camera. To view additional information on the current photograph, press 1 and 3 (0 187). P button Image area..... Highlight NEF (RAW) processing in the retouch menu and press 2 to display a picture selection dialog listing only NEF (RAW) images created with this camera. Page 15 Basic Photography and Playback Battery Level and Card Capacity .....35 "Point-and-Shoot" Photography (i and j Modes) .....36 Basic Playback .....39 Deleting Unwanted Photographs.....40 Creative Photography (Scene Modes) .....41 k Portrait.....41 l Landscape.....41 p Child.....42 m Sports.....42 n Close Up.....42 o Night Portrait .....42 r Night Landscape.....43 s Party/Indoor .....43 t Beach/Snow .....43... Press J or press the shutter-release button all the way down to measure white balance. Option Description Enable wireless connections to smart devices running the Wireless Mobile Enable Utility. Save/Load Settings G button B setup menu Select Save settings to save the following settings to the memory card in Slot 1 (0 69; if the card is full, an error will be displayed). Page 309 Adjust gain. f6: Release Button to Use Dial G button A Custom Settings menu If Yes is selected, adjustments that are normally made by rotating the command dial while holding a button can instead be made by rotating the command dial after the button is released (setting ends when the button is pressed again, the shutter-release button is pressed halfway, or the standby timer expires). Ved veldig kaldt eller varmt vær kan du merke at batteriet tømmes raskere. Page 220 Overview Data NIKON D7100 1 4000 F2 . If the camera is connected to the computer, turn the camera off and disconnect the USB cable. e Microphone sensitivity Microphone sensitivity for movie recording. Page 136 Picture Control Settings Option Description Choose from options between –2 and +2 to reduce or exaggerate the effect of the selected Picture Control by adjusting sharpening, contrast, and Quick adjust saturation (note that this resets all manual adjustments). Virtual Horizon G button B setup menu Display a virtual horizon based on information from the camera tilt sensor. Page 81 Choose a shutter speed. Press J to display the options shown at right (note that the options temporarily clear from the display during autofocus). Camera Menus Most shooting, playback, and setup options can be accessed from the camera menus. Mode dial lock release Special Effects Modes (0 177) Use special effects during shooting. Page 330 Calculating Angle of View The size of the area exposed by a 35mm camera is 36 × 24 mm. Color Balance G button N retouch menu Use the multi selector to create a copy with modified color balance as shown below. To enter a folder number, choose Select folder by number, enter the number (0 225), and press J. Page 166 Select a white balance increment. Flash Compensation (P, S, A, and M Modes Only) Flash compensation is used to alter flash output by from –3EV to +1EV in increments EV, changing the brightness of the main subject relative to the background. Recalling User Settings Mode dial Simply rotate the mode dial to U1 to recall the settings assigned to Save to U1, or to U2 to recall the settings assigned to Save to U2. The Memory Buffer Regardless of the option selected for Custom Setting d6, shooting will slow when the memory buffer fills (t00). Page 151 Aperture, Sensitivity, and Flash Range Flash range varies with sensitivity (ISO equivalency) and aperture. At default settings, all the pictures on the memory card will be copied to the computer. The effect can be previewed in the edit display. First Steps Charge the Battery The camera is powered by an EN-EL15 rechargeable Li-ion battery (supplied). Format Memory Card G button B setup menu To begin formatting, choose a memory card slot and select Yes. Information on Information off Virtual horizon Framing guides (0 269) Manual Focus To focus in manual focus mode (0 78), rotate the lens focus ring until the subject is in focus. The camera will vary exposure and/or flash level shot-by- shot according to the bracketing program selected. Notices • No part of the manuals included with this • Nikon will not be held liable for any product may be reproduced, transmitted, damages resulting from the use of this transcribed, stored in a retrieval system, or product. 177–183 Can I adjust shutter speed to freeze or blur motion (mode S)? If On (Auto reset) or On is selected, the 0 at the center of the exposure display will flash even when exposure compensation is set to ±0. flash and AF-assist illuminator turn off. High Dynamic Range (HDR) (P, S, A, and M Modes Only) Used with high-contrast subjects, High Dynamic Range (HDR) preserves details in highlights and shadows by combining two shots taken at different exposures. The built-in flash turns off; use of a tripod is recommended when lighting is poor. Page 11 e Bracketing/flash f Controls e1 Flash sync 1/320 s (Auto FP) OK button Shooting mode speed 1/250 s (Auto FP) Playback mode 1/250 s (default) Live view 1/200 s Assign Fn Press button 1/160 s Press + command dials 1/125 s Assign Press preview... Before going on to select or deselect individual images, you can mark all or all protected images in the folder for copying by choosing Select all images or Select protected images. Page 115 Mode M In mode M, exposure compensation affects only the exposure indicator; shutter speed and aperture do not change. Click Start Transfer. Page 174 Choose the number of intervals and number of shots per interval. 3 85mm 0, 0 + 1 . TO THE MAXIMUM EXTENT PERMITTED UNDER APPLICABLE LAW, NIKON, ITS EMPLOYEES, DISTRIBUTORS, DEALERS, AND AGENTS DO NOT WARRANT THE PERFORMANCE OF OR THE RESULTS YOU MAY OBTAIN FROM THE MANUAL, OR THAT THE MANUAL WILL MEET YOUR REQUIREMENTS OR THAT THE OPERATION OF THE MANUAL WILL BE UNINTERRUPTED, ERROR-FREE, OR FREE OF VIRUSES. Choose Enable to upload photographs to a preselected destination (if two Eye-Fi cards are inserted, you can choose the card used for upload). Turn the printer on and connect the USB cable as shown. b3: Easy Exposure Compensation G button A Custom Settings menu This option controls whether the E button is needed to set exposure compensation (0 86). AF Fine-tune G button B setup menu Fine-tune focus for up to 12 lens types. The shutter can be released at any time regardless of the options selected for Custom Settings a1 (AF-C priority selection, 0 231) and a2 (AF-S priority selection, 0 231), and the in-focus indicator (I) will not be displayed in the viewfinder. h mode Main command dial Monitor Choose a special effect mode (q; 0 177). Live View Photography Follow the steps below to take photographs in live view. 12 If maximum aperture is specified using Non-CPU lens data (0 149), aperture value will be displayed in viewfinder and control panel. To install a memory card, turn the camera off and, holding the card in the orientation shown below, slide it in until it clicks into place. Sound level for audio recording. Press 1 or 3 to highlight a date. The monitor turns off when the shutter-release button is pressed. Du finner svar på ofte stilte spørsmål på denne siden, og kan kontakte La oss få vite hva du syns om Nikon D7100 Digitalkamera ved å gi en produktbedømmelse. If dust can not be fully removed using the options in the Clean image sensor menu, clean the image sensor manually (0 315) or consult a Nikon-authorized service representative. Highlight a folder. Ingen kopiering eller reproduksjon av noen art skal foretas av denne veiledningen, hverken i sin helhet eller av enkeltdeler (med unntak av korte henvisninger i artikler eller anmeldelser) uten skriftlig godkjennelse fra NIKON CORPORATION.Besøk siden under for å registrere kameraet ditt og holde deg oppdatert om den siste produktinformasjonen. 273–290 How do I remove "red-eye"? P button Viewfinder Photography Press P to view links to frequently-used shooting options at the bottom of the information display (0 12). Custom Setting e4 (Exposure comp. Press J to return to live view. Highlight Movie settings in the shooting menu and press 2. Page 210 u Selective Color Press the a button. Hold W (S) button and press 4 or 2 to cycle through channels as follows: (all channels) (red) Page 217 Playback Zoom To zoom in on the photograph when the histogram is displayed, press X (T). Page 353 Custom Settings Menu Defaults Option Default Option Default a1 AF-C priority selection Release d12 MB-D15 battery type LR6 (AA alkaline) 242 a2 AF-S priority selection Focus Use MB-D15 Battery order batteries first a3 Focus tracking with lock-on 3 (Normal) e1 Flash sync speed 1/250 s a4 AF point illumination Auto... Battery/Display The camera is on but does not respond: Wait for recording to end. Non-CPU lens number selection can be assigned to the Fn button (Custom Setting f2, Assign Fn button, 0 253), the depth-of-field preview button (Custom Setting f3, Assign preview button, 0 255), or the A AE-L/AF-L button (Custom Setting f4, Assign... Date list W (S) W (S) X (T) X (T) Thumbnail list Full-frame Thumbnail playback Calendar playback playback The operations can be performed depend on whether the cursor is in the date list or the thumbnail list: Description Press W (S) or J button in date list to place cursor in... e5: Modeling Flash G button A Custom Settings menu If On is selected when the camera is being used with the built-in flash or an optional CLS-compatible flash unit (0 305), a modeling flash will be emitted when the camera depth-of-field preview button is pressed (0 50). Insert the Battery Before inserting the battery, rotate the power switch to OFF. Using Two Memory Cards When two memory cards are inserted in the camera, you can use the Role played by card in Slot 2 item in the shooting menu to choose the role played by the card in Slot 2. Auto ISO Sensitivity Control (P, S, A, and M Modes Only) If On is selected for ISO sensitivity settings > Auto ISO sensitivity control in the shooting menu, ISO sensitivity will automatically be adjusted if optimal exposure can not be achieved at the value selected by the user (ISO sensitivity is adjusted appropriately when the flash is used). • Turn the power off before inserting or removing memory cards. Exposure Metering (P, S, A, and M Modes Only) Choose how the camera sets exposure in P, S, A, and M modes (in other modes, the camera selects the metering method automatically). For eksempel har et kamera som lager bilder på 1280 x 960 piksler, en oppløsning på omtrent 1,3 MP. Aperture at ISO equivalent of Approximate range 1600 3200 6400 0.7–8.5 2 ft 4 in.–27 ft 11 in. Page 363 Indicator Control Monitor panel Problem Solution Select folder containing No images on memory images from Playback folder Folder contains no — card or in folder(s) 30, 217 menu or insert memory card images. G button The playback menu contains the following options: Option Option Delete Image review Playback folder After delete Hide image Rotate tall Playback display options... Se manualen for Nikon D7100 gratis, eller still spørsmål til andre eiere av Nikon D7100. Page 7 Insert a memory card (0 30). Press 1 or 3 to move the item up or down in My Menu and press J. Auto FP High-Speed Sync When 1/320 s (Auto FP) or 1/250 s (Auto FP) is selected for Custom Setting e1 (Flash sync speed, 0 244), the built-in flash can be used at shutter speeds as fast as s or s, while compatible optional flash units (0 305) can be used at any shutter speed (Auto FP High-Speed Sync). Windows To visit the Nikon website after installing ViewNX 2, select All Programs > Link to Nikon from the Windows start menu (Internet connection required). Image Dust Off ref photo is available only when a CPU lens is mounted on the camera. Page 4 Q&A Index Find what you're looking for using this "question and answer" index. Hide Image G button D playback menu Hide or reveal pictures. Page 219 8 The fourth page of the shooting data is only displayed if copyright information was recorded with the photograph as described on page 267. If the subject is poorly lit, the flash may pop up and the AF-assist illuminator may light. If desired, additional pictures can be taken without releasing FV lock. Highlight v Auto, c Extra high, S High, T Normal, or U Low and press J. User Settings: U1 and U2 Modes Assign frequently-used settings to the U1 and U2 positions on the mode dial. The AF- natural light before dawn or after sunset. Press the L (U) button and rotate the sub-command dial until the desired white balance preset (d-1 to d-6) is displayed in the control panel. Choose ADL bracketing for Custom Setting e6 Auto bracketing set. Wireless remote sensors 60° or less 5 m/15 ft or on flash units should face less 10 m/33 ft or less... Page 344 Remove any dust and lint from the sensor with a blower. 66 Image Size .....68 Using Two Memory Cards .....69 Focus Autofocus .....71 Autofocus Mode .....71 AF-Area Mode..... • Recharge or replace battery. f4: Assign AE-L/AF-L Button G button A Custom Settings menu Choose the role played by the A AE-L/AF-L button, either by itself (Press) or when used in combination with the command dials (Press + command dials). Special Effects Special effects can be used when recording images. The Information Display: Live View Photography To hide or display indicators in the monitor during live view photography, press the R button. 218 Playback Display Options..... Slide the AC wall adapter latch in the direction shown (w) and rotate the adapter 90°... Display the menus. Reset Custom Settings G button A Custom Settings menu Select Yes to restore Custom Settings to their default values (0 325). Rotate the live view selector to 1 (movie live view). The D7100, however, is designed to be used with interchangeable lenses, and foreign matter may enter the camera when lenses are removed or exchanged. Reduce size of crop X (T) Press X (T) to increase the size of the crop. Self-Timer Mode The self-timer can be used to reduce camera shake or for self-portraits. Foreign Matter on the Image Sensor Nikon takes every possible precaution to prevent foreign matter from coming into contact with the image sensor during production and shipping. 265 Language ..... D button Main command dial Control panel Select bracketing increment... Indicators in the monitor and on the HDMI device can be hidden or displayed using the R button. The camera does not emit monitor pre- 2 Manual flashes. Page 88 Cover the Viewfinder DK-23 rubber eyecup DK-5 eyepiece cap When taking photos without your eye to the viewfinder, remove the DK-23 rubber eyecup (q) and insert the supplied DK-5 eyepiece cap as shown (w). Delete frames. Do not use a blower-brush, as the bristles could damage the sensor. Adjust settings. Use slow shutter speeds to suggest motion by blurring moving subjects, fast shutter speeds to "freeze" motion. Page 167 ADL Bracketing The camera varies Active D-Lighting over a series of exposures. This prevents light entering via the viewfinder interfering with exposure. Press the Fn button to release FV lock. Display the photograph. Photographs with an aspect ratio of 16 : 9 (0 163) can not be resized. To view six pictures at a time, press the W (S) button. Highlight an option. B The Setup Menu: Camera Setup To display the setup menu, press G and select the B (setup menu) tab. Megapiksler brukes blant annet til å angi oppløsningen på digitalkameraer og videokameraer. Page 357 Photos are out of focus: • Rotate focus-mode selector to AF (0 71). Number of Number Total intervals of shots/ number of interval shots... Det var nyttig (285) Les mer Nei, dette er ikke nødvendig. Velg ditt foretrukne språk på hjemmesiden vår og søk etter modellnummeret for å se om vi har det tilgjengelig. Exposure Compensation (P, S, A, M and % Modes Only) Exposure compensation is used to alter exposure from the value suggested by the camera, making pictures brighter or darker. Use the multi selector to position the focus point in the area that will be in focus and then press the shutter-release button halfway to focus (note that the options temporarily clear from the display during autofocus). Available Settings The following table lists the settings that can be adjusted in each mode. Release the L (U) button briefly and then press the button until the L icon in the control panel starts to flash. W (S) button Sub-command dial Control panel Exposure Choose a combination of aperture and shutter speed (mode P; 0 48). Page 325 The AF-S/AF-I Teleconverter The AF-S/AF-I teleconverter can be used with the following AF-S and AF-I lenses: • AF-S NIKKOR 70–200mm f/2.8G ED VR II • AF-S 300mm f/4D ED • AF-S VR 70–200mm f/2.8G ED • AF-S NIKKOR 400mm f/2.8G ED VR •... Page 18 Special Effects Shooting with Special Effects..... Camera Zoom position Minimum distance without vignetting... Press 4 or 2 to view additional pictures. Page 227 Press J to complete the operation. M (Y) button Main command dial Control panel Set flash compensation (mode P, S, A, or M; 0 124). Press the G button to display the menus. Page 190 Focus. Mounting mark (lens) If the lens is equipped with an A-M or M/A-M mode switch, select A (autofocus) or M/A (autofocus with manual override). More on Playback Full-Frame Playback To play photographs back, press the K button. After adjusting filter effects as described below, press J to copy the photograph. Make the initial selection. Open the battery-chamber (q) and power connector (w) covers. "Times"... Det var nyttig (191) Les mer Download Nikon D7100 User Manual or view PDF for FREE. Page 32 The Camera Body (Continued) AF-assist illuminator.....233 Contact cover for optional MB-D15 battery pack Self-timer lamp.....59 .....308 Red-eye reduction lamp .....121 Power connector cover .....311 Sub-command dial.....13, 257 CPU contacts Depth-of-field preview button..50, 255, 260 Lens mount .....27, 78 Fn (function) button .. Be sure to insert the connector in the orientation shown, using the connector to keep the orange battery latch pressed to one side. Select the source folder. Frame Advance Rate The frame rate for continuous shooting (low and high speed) varies with the option chosen for image area (0 63) and, when an NEF (RAW) image quality option is selected, the NEF (RAW) bit depth (0 67). Before Shooting Do not select self-timer (E) or M release mode when using the interval timer. a button Position the focus point. Format the Memory Card Memory cards must be formatted before first use or after being used or formatted in other devices. In full-frame playback, select a retouched copy (shown by a o icon) or a photograph that has been retouched and press P. The Auto option in the White balance menu offers a choice of Normal and Keep warm lighting colors, which preserves the warm colors produced by incandescent lighting, while the I Fluorescent option can be used to select the light... Select m Recent settings. Manuals and User Guides for Nikon D7100. Night Landscape Party/Indoor Reduce noise and unnatural colors when Capture the effects of indoor photographing night landscapes, background lighting. Press 1 or 3 to highlight an option. In My Menu (O), highlight Remove items and press 2. Image Review G button D playback menu Choose whether pictures are automatically displayed in the monitor immediately after shooting. Page 244 HDMI Options The HDMI option in the setup menu (0 261) controls output resolution and can be used to enable the camera for remote control from devices that support HDMI-CEC (High-Definition Multimedia Interface–Consumer Electronics Control, a standard that allows HDMI devices to be used to control peripherals to which they are connected). G button Choose an option. Page 350 k, p, l, m, n, o, r, t, x, y, u, 1, S, A, i j P u, v w z, 0 % g i 2, 3 z z z z z z a1: AF-C priority selection z z z z z z a2: AF-S priority selection a3: Focus tracking with... 313 DPOF print order.....213 Focus point Clock ..... Det er også lurt å sørge for at batteriet er omtrent 67% ladet før det lagres. prevent blur when lighting is poor. 3... 100% horizontal and 100% vertical –1 Magnification Approx. Page 384 No reproduction in any form of this manual, in whole or in part (except for brief quotation in critical articles or reviews), may be made without written authorization from NIKON CORPORATION. Page 42 Scene and Special Effect Modes Choose a scene (h; 0 41). Page 21 B The Setup Menu: Camera Setup .....261 Format Memory Card..... Front Slot 1 Slot 2 Turn the camera on. No images can be played back until another folder has All images are All photos in current... The default value is 1.0; select 0.5 to halve gain or 2.0 to double it. 1 icon Length Current position/total length Movie progress bar Volume Guide The following operations can be performed: Description Pause Pause playback. 247 100 - 1 NIKON D7100 Flash mode.....120 Flash control .....246, 305, 306 Flash compensation.....124 Camera name Image area.....63 Folder number—frame number ....225 White balance .....89... Miniature Effect G button N retouch menu Create a copy that appears to be a photo of a diorama. Move cursor up J button: select highlighted item Cancel and return to Select highlighted item or previous menu display sub-menu Move cursor down Follow the steps below to navigate the menus. Page 233 Do not turn the camera off or disconnect the USB cable while transfer is in progress. Page 178 The camera can store data for up to nine non-CPU lenses. After Delete G button D playback menu Choose the picture displayed after an image is deleted. Select Choose image area as the "press + command dials" option for a camera control in the Custom Settings menu (0 229). Storage Folder G button C shooting menu Select the folder in which subsequent images will be stored. — w Headphone volume Volume of audio output to headphones. Choose in situations in which it is difficult to set exposure, flash level (i-TTL and, where supported, auto aperture flash control modes only;... W (S) View thumbnails See page 193 for more information. Page 43 ISO Sensitivity Set ISO sensitivity (0 79). Choose page size, border, and time stamp options as described on page 209 (a warning will be displayed if the selected page size is too small for an index print). (0 264). Clothing Fast shutter speeds freeze motion for and background details are vividly dynamic sports shots in which the main rendered, while skin tones remain soft subject stands out clearly. JPEG Compression Choose the type of compression for JPEG images. Option Description Start slide show. 238 ADL bracketing amount .....139 Copyright information .....267 Image comment indicator ..... Can I use special effects during shooting? For information on focusing manually, see page 159. 35–38 How do I quickly adjust settings for different scenes? Page 120 Press J. Page 345 End cleaning or inspection immediately. Det var nyttig (199) Les mer Litiumionbatterier fungerer optimalt ved en temperatur mellom 5 og 45 grader Celsius. To take the photograph, press the shutter-release button the rest of the way down. Page 329 AF-Assist Illumination AF-assist illumination is not available with the following lenses: • AF-S NIKKOR 14–24mm f/2.8G ED • AF-S VR Zoom-Nikkor 200–400mm f/4G • AF-S NIKKOR 200mm f/2G ED VR II IF-ED • AF-S VR Nikkor 200mm f/2G IF-ED • AF-S NIKKOR 200–400mm f/4G ED VR II •... battery. Repeat Steps 1–4 to select additional items. Page 277 Compose the shot. Choosing a Color Temperature When K (Choose color temp.) is selected for white balance, color temperature can be selected by pressing the L (U) button and rotating the sub- command dial. Press J to save settings and return to the shooting menu. Note that matrix metering will not produce the desired results. Adjust Viewfinder Focus The camera is equipped with diopter adjustment to accommodate individual differences in vision. Highlight items using the multi selector and press 2 to view options for the highlighted item. FV Lock This feature is used to lock flash output, allowing photographs to be recomposed without changing the flash level and ensuring that flash output is appropriate to the subject even when the subject is not positioned in the center of the frame. Using a GPS Unit An optional GP-1 GPS unit can be connected to the camera's accessory terminal (0 310) using the cable supplied with the GPS unit, allowing information on the camera's current position to be recorded when photographs are taken. Mirror up Mode Choose this mode to minimize blurring caused by camera movement when the mirror is raised. Open the battery-chamber cover. Before beginning interval timer photography, take a test shot at current settings and view the results in the monitor. If error persists or appears frequently, consult Camera malfunction. 265 Auto Image Rotation..... • Frame size/frame rate, Movie quality: Choose from the following options: Frame size/frame rate Movie quality Maximum length Maximum bit rate (Mbps) (high quality/Normal) Frame size (pixels) Frame rate (high quality/Normal) Page 198 Select Movie settings. Computer displays NEF (RAW) images differently from camera: Third-party software does not display effects of Picture Controls or Active D-Lighting. Shutter speed can be set to "v" or to values between 30 s and s, or 8000 the shutter can be held open indefinitely for a long time-exposure... AF fine-tune •... Use for parties and including street lighting and neon signs. 63 High ISO noise reduction.....228 Active D-Lighting ..... Option Description Matrix: Produces natural results in most situations. • Reverse rotation: Reverse the direction of rotation of the command dials when they are used to make adjustments to Exposure compensation and/or Shutter speed/aperture. Page 276 Follow the steps below to take photographs in commander mode. View additional pictures. Page 373 Supplied Accessories • 67 mm Snap-on Front Lens Cap LC-67 • Rear Lens Cap • Flexible Lens Pouch CL-1018 • Bayonet Hood HB-32 (attaches as shown at right) Optional Accessories • 67 mm screw-on filters • Rear Lens Cap LF-1 or Rear Lens Cap LF-4 A Note on Wide-Angle Lenses Autofocus may not provide the desired results with wide–... Highlight the desired preset and press W (S). The active focus point will be displayed. Calendar Playback To view images taken on a selected date, press the W (S) button when 72 images are displayed. Selected color Select a color. Page 184 Choosing an AF-Area Mode In modes other than i, the following AF-area modes can be selected in live view (note that subject-tracking AF is not available in %, g, and u modes): Mode Description Face-priority AF: Use for portraits. Before After Color Sketch G button N retouch menu Create a copy of a photograph that resembles a sketch made... Exit the installer. GPS data are only displayed if a GPS unit was used when the photo was taken. Before shooting, mount the camera on a tripod or place the camera on a stable, level surface. • An extremely exhausted • Replace the battery, or xxvi, 22, rechargeable Li-ion battery... If a copy can not be created at the current playback position, the current position will be displayed in red in Step 5 and no copy will be created. Mode dial To shoot where use of a flash is prohibited, photograph infants, or capture natural lighting... The camera automatically detects and focuses on portrait subjects;... Attaching a Power Connector and AC Adapter Turn the camera off before attaching an optional power connector and AC adapter. Saving Selected Frames To save a copy of a selected frame as a JPEG still: View the movie and choose a frame. • Bulb (A): The shutter remains open while the shutter-release button is held down. Frame Size and Rate Frame size and rate affects the distribution and amount of noise (randomly-spaced bright pixels, fog, or bright spots). A Custom Settings: Fine-Tuning Camera Settings To display the Custom Settings menu, press G and select the A (Custom Settings menu) tab. 0.6–4.2 2 ft–13 ft 9 in. Page 142 To use Active D-Lighting: Select Active D-Lighting in the shooting menu. Flash unit SB-80DX, SB-28DX, SB-28, SB-30, SB-27 , SB-22S, SB-23, SB-29 Flash mode SB-26, SB-25, SB-24 SB-50DX SB-22, SB-20, SB-16B, SB-15 SB-21B , SB-29S —... 36 a (Live view) button . Creating Custom Picture Controls The Picture Controls supplied with the camera can be modified and saved as custom Picture Controls. Exposure The following settings can be adjusted in movie live view: Aperture... Mode P Main command dial Control panel... C AE lock only Exposure locks while the MB-D15 A AE-L/AF-L button is pressed. Ready the camera. Du kan alltid laste ned bruksanvisningen fra nettsiden vår og skrive den ut selv. Dra til en Repair Café for gratis hjelp til reparasjon. SD-kort er standard lagringsmedium for mange digitale kameraer. Choose Highlight Select folder by number and press 2. The effect can be chosen during live view (0 182). 0 The Index..... Protected files can not be deleted using the O (Q) button or the Delete option in the playback menu. The location of the current image is shown by an icon at the bottom left corner of the display. Note that output level can not be adjusted in – – mode. Child Sports Use for snapshots of children. Connecting the Printer Connect the camera using the supplied UC-E6 USB cable. Menu Options D PLAYBACK MENU (0 217) C SHOOTING MENU (0 224) Delete Reset shooting Selected menu Select date Storage folder Select folder by number Playback folder D7100 (default) Select folder from list File naming File naming Role played by Current Overflow (default) Set Picture Interval timer Standard (default) Choose start time Control shooting Neutral Vivid Start time Monochrome Interval Portrait Select no. 0.6–3.0 2 ft–9 ft 10 in. d3: ISO Display and Adjustment G button A Custom Settings menu If Show ISO sensitivity or Show ISO/Easy ISO is selected, the control panel will... For more information on Active D-Lighting, see page 113. 2. Page 191 End recording. Choose from # Large, $ Medium, or % Small (note that image size varies depending on the option selected for Image area, 0 63): Image area Option Size (pixels) Print size (cm/in.) Large 6000 ×... Page 19 Menu Guide D The Playback Menu: Managing Images .....217 Playback Folder..... Do not use force or attempt to insert the connectors at an angle. AF-Area Mode Choose how the focus point for autofocus is selected. Option Description C 5 (Long) a6: Number of Focus Points G button A Custom Settings menu Choose the number of focus points available for manual focus-point selection. Highlight Manage Picture Control in the shooting menu and press 2. a: Autofocus a1: AF-C Priority Selection G button A Custom Settings menu When AF-C is selected for viewfinder photography (0 71), this option controls whether photographs can be taken whenever the shutter-release button is pressed (release priority) or only when the camera is in focus (focus priority). Each division is equivalent to 5°. a button Display options. 0 Intro

folder containing the images to be copied and press 2. Press 1 or 3 to highlight a folder. K button Multi selector Sub-command dial O (Q) button K button G button L (U) button X (T) button W (S) button P button J button... Auto If the mode dial is rotated to P, S, A, or M after Auto is selected for ISO sensitivity in another mode, the ISO sensitivity last selected in P, S, A, or M mode will be restored. A segment will disappear from the indicator after each shot: if the bracketing program contains two shots, the indicator will change from , while if the program contains three... If the folder with the selected number does not already exist, a new folder will be created. Eye-Fi Upload G button B setup menu This option is displayed only when an Eye-Fi memory card (available separately from third-party suppliers) is inserted in the camera. N The Retouch Menu: Creating Retouched Copies To display the retouch menu, press G and select the N (retouch menu) tab. Other playback operations that use the P button, such as Side-by-side comparison (0 290), can not be performed even if the camera is not currently connected to a network. Page 365 Viewfinder Viewfinder Eye-level pentaprism single-lens reflex viewfinder Frame coverage Approx. To hide all pictures taken on a date, highlight the date and press 2. Highlight EXE and press J to create a JPEG copy of the selected photograph (to exit without copying the photograph, press the G button). The Control Panel MB-D15 battery indicator.....243 Battery indicator ..... Continuous low speed: While shutter-release button is held down, camera takes photographs at frame rate selected for Custom Setting d5 (CL mode shooting speed, 0 58, 239). 268 Time stamp (PictBridge) .... • Camera unable to focus using autofocus: use manual focus or focus lock (0 76, 78). The desired results may not be achieved if the camera or subject moves during shooting. Option Description Auto FP high-speed sync is used when a compatible flash unit is attached (0 305). b4: Center-Weighted Area G button A Custom Settings menu When calculating exposure, center-weighted metering assigns the greatest weight to a circle in the center of the frame. f9: Assign MB-D15 4 Button G button A Custom Settings menu Choose the function assigned to the A AE-L/AF-L button on the optional MB-D15 battery pack. Main Bulb command dial Time Open the shutter. Select the highlighted item. Release shutter. Wireless Remote Controllers When the camera is used with optional WR-1 (0 309) and WR-R10/WR-T10 (0 309) wireless remote controllers, the shutter-release buttons on the WR-1 and WR-T10 perform the same functions as the camera shutter-release button, allowing remote continuous and self-timer photography. The Release Mode Dial Release mode dial lock release To choose a release mode, press the release mode dial lock release and turn the release mode dial to the desired setting (0 57). Press 1 or 3 to increase or decrease the range of similar hues that will be included in the final photograph. Mode Description Programmed auto (0 48): Camera sets shutter speed and aperture for optimal exposure. Page 351 k, p, l, m, n, o, r, t, x, y, u, 1, S, A, i j P u, v w z, 0 % g i 2, 3 z z z z z z e1: Flash sync speed — — z e2: Flash shutter speed —... All rights reserved. Depending on the scene, the effect many not be visible, shadows may appear around bright objects, or halos may appear around dark objects. Select a preset. Image Enhancement Picture Controls (P, S, A, and M Modes Only) Nikon’s unique Picture Control system makes it possible to share image processing settings, including sharpening, contrast, brightness, saturation, and hue, among compatible devices and software. L (U) button Sub-command dial Control panel... Note that the number of subjects that can be detected in face-priority AF drops in movie live view. Attach the strap securely to the camera eyelets. Page 182 Take the picture. Page 171 Choose the amount of gain. Negative voltages or voltages over 250 V applied to the accessory shoe could not only prevent normal operation, but damage the sync circuitry of the camera or flash. Dusk/Dawn Pet Portrait Preserves the colors seen in the weak Use for portraits of active pets. Page 249 Select a destination folder. Highlight a date. Turn the camera on. Flicker or banding appears during live view or movie recording: Choose an option for Flicker reduction that matches the frequency of the local AC power supply (0 264). Page 196 HDMI If the camera is connected to an HDMI device (0 215), the view through the lens will appear both in the camera monitor and on the HDMI device. Taking a Closer Look: Playback Zoom Press the X (T) button to zoom in on the image displayed in full-frame playback or on the image currently highlighted in thumbnail playback. 0 – 1. Press the G button and select DPOF print order in the playback menu. 6 1 125 85mm 0, 0 100D7100 DSC _ 0001 . The dialog shown at right will be displayed; highlight pictures using the multi selector and press the W (S) button to select or deselect (to view the highlighted picture full screen, press and hold the X (T) button;... Press the shutter-release button the rest of the way down to shoot. Page 162 Select a bracketing increment. Page 26 Nikon may cause harmful interference to radio Corporation may void the user’s authority to communications. Remove the lens cap and turn the camera on. Rusting of the internal mechanism can cause irreparable damage. Page 145 Framing HDR Photographs The edges of the image will be cropped out. To exit live view, press the a button again. Page 216 Highlights Image highlights 100 - 1 Folder number—frame number ....225 Current channel Select R, G, B Highlights * Flashing areas indicate highlights (areas that may be overexposed) for the current channel. Page 92 Image area can be set using the Image area option in the shooting menu or by pressing a control and rotating a command dial (0 65). Can I trim movie footage on the camera or save movie stills? Page 59 Memory Cards • Memory cards may be hot after use. O My Menu/m Recent Settings To display My Menu, press G and select the O (My Menu) tab. G button Custom Setting groups Custom Settings are used to customize camera settings to suit individual preferences. Ready a fully-charged spare Low battery. Filter Effects G button N retouch menu Choose from the following filter effects. Note that the maximum distance at which the remote flash units can be placed may vary with shooting conditions. g3: Assign AE-L/AF-L Button G button A Custom Settings menu Choose the role played by the A AE-L/AF-L button during movie live view. Highlight the desired item and press 2, then highlight an option and press J. Frame an object in the white square in the center of the display and press 1 to choose the color of the object as one that will remain in... Movie Settings Use the Movie settings option in the shooting menu to adjust the following settings. Mounting mark Keeping marks (indicated by white dot) aligned, position (camera) lens on camera, then rotate until lens clicks into place. Selecting Folders from a List Choose Select folder from list. Movie Live View Movies can be recorded in live view. Det var nyttig (223) Les mer Ja, enheten kan fortsatt brukes trygt. Highlight one of the following and press J. If v Auto is selected, the camera will automatically adjust HDR strength according to shooting conditions. Nikon Software ViewNX 2 (supplied) and Capture NX 2 (available separately) automatically select the correct color space when opening photographs created with this camera. Defaults The default settings for the options in the camera menus are listed below. GPS Data Latitude Longitude Altitude º ’ º ’ Coordinated Universal Time (UTC) 100 - 1 NIKON D7100 * Data for movies are for start of recording. W (S) button Main command dial Control panel Set auto ISO sensitivity control (0 82). Frame a photograph in the viewfinder with the main subject in the AF area brackets. Hidden pictures are visible only in the Hide image menu and can only be deleted by formatting the memory card. Page 321 Reordering Options in My Menu Select Rank items. Insert the battery. Windows Mac OS Click Yes Click OK The following software is installed: • ViewNX 2 • Apple QuickTime (Windows only) Remove the installer CD from the CD-ROM drive. Page 93 Camera Controls Assign image area selection to a camera control. If image sensor cleaning is performed several times in succession, image sensor cleaning may be temporarily disabled to protect the camera’s internal circuitry. Choosing a scene mode automatically optimizes settings to suit the selected scene, making creative photography as simple as selecting a mode, framing a picture, and shooting as described on pages 36–38. G button The shooting menu contains the following options: Option Option Reset shooting menu Color space Storage folder Active D-Lighting File naming HDR (high dynamic range) Role played by card in Slot 2... The camera can store up to six values for preset white balance in presets d-1 through d-6. Page 65 Frame the photograph. Interval Timer Photography The camera is equipped to take photographs automatically at preset intervals. 73 Focus Point Selection.....75 Focus Lock.....76 Manual Focus .....78 ISO Sensitivity Auto ISO Sensitivity Control .....81 Exposure... Cover the Viewfinder To prevent light entering via the viewfinder from interfering with exposure, remove the rubber eyecup and cover the Live view selector viewfinder with the supplied DK-5 eyepiece cap before shooting (0 60). Page 362 Camera cannot detect Turn camera off and confirm No memory card. Page 131 Protecting a White Balance Preset Follow the steps below to protect the selected white balance preset. Page 202 Select Choose start/end point. The Camera Body Release mode dial.....7, 57 Movie-record button ..... Basic Photography and Playback Battery Level and Card Capacity Before shooting, check the battery level and number of exposures remaining. Long Exposure NR G button C shooting menu (Long Exposure Noise Reduction) If On is selected, photographs taken at shutter speeds slower than 1 s will be processed to reduce noise (bright spots, randomly-spaced bright pixels, or fog). 295 Optional Flash Units (Speedlights)..... If an optional flash unit is attached in shooting modes other than j, %, and u, the flash will fire with every shot, even in modes in which the built-in flash can not be used. Inserting and Removing Batteries Always turn the camera off before inserting or removing batteries. 219 Copy Image(s).....219 Image Review .....222 After Delete .....222 Rotate Tall ..... Nikon will not be held liable for damages or lost profits that may result from product malfunction. The selected settings will continue in effect and will apply to photographs taken using the viewfinder. & Remote Control Photography Using an Optional ML-L3 Remote Control The optional ML-L3 remote control (0 309) can be used to reduce camera shake or for self-portraits. Page 242 Select imprint options. If Off is selected, pictures can only be displayed by pressing the K button. The camera clock is automatically set to the time in Time zone the new time zone. 58, 239 Exposure indicator .....51 Exposure compensation display..... Using Camera Menus The multi selector and J button are used to navigate the camera menus. g2: Assign Preview Button G button A Custom Settings menu Choose the role played by the depth-of-field preview button during movie live view. Pictures are recorded using a 18.8 × 12.5 mm image area, producing a telephoto effect without the need to change lenses (0 68, 167). 265 Battery Info .....266 Image Comment..... Page 214 Description View additional Press 2 to view photographs in order recorded, 4 to view photographs photographs in reverse order. Auto white balance is recommended for most light sources in P, S, A, and M modes, but other values can be selected if necessary according to the type of source: Option... To display the menus, press the G button. a3: Focus Tracking with Lock-On G button A Custom Settings menu This option controls how autofocus adjusts to sudden large changes in the distance to the subject when AF-C is selected or continuous-servo autofocus is selected when the camera is in AF-A mode for viewfinder photography (0 71). Display the photograph you wish to delete as described on the preceding page. Insert the EP-5B power connector. Be sure to copy any photographs and other data you wish to keep to a computer before proceeding (0 203). button Position the subject in the selected focus point and press the shutter-release button halfway. To delete multiple selected photographs, all photographs taken on a selected date, or all photographs in the current playback folder, use the Delete option in the playback menu. Turn the camera off before connecting the GPS unit;... Vil du dele dine erfaringer med dette produktet eller stille et spørsmål? Nedenfor kan du se og laste ned PDF-bruksanvisningen gratis på norsk. Resume playback when movie is paused or during rewind/ Play advance. Page 348 • Continuing to charge the battery after it is fully charged can impair battery performance. All other trade names mentioned in this manual or the other documentation provided with your Nikon product are trademarks or registered trademarks of their respective holders. Use the X (T) and W (S) buttons to zoom in and out and scroll the image with the multi selector. Page 17 Flash Photography Using the Built-in Flash..... Deleting Options from My Menu Select Remove items. This mode is recommended for snapshots and other situations in which you want to leave the camera in charge of shutter speed and aperture. Viewfinder virtual Press the Fn button to view a virtual horizon display in the viewfinder. 37, 73, 75, 78, 156, 232, 233 Clock battery .....29 Dynamic-area AF.....73, 74 Focus point wrap-around ..232 Cloudy (White balance) ....89 Focus tracking ..... The Nikon Creative Lighting System (CLS) Nikon’s advanced Creative Lighting System (CLS) offers improved communication between the camera and compatible flash units for improved flash photography. Confirm that the FV lock icon (e) is no longer displayed in the viewfinder. Page 317 Choose the color range. W (S) W (S) X (T) X (T) Full-frame Calendar Thumbnail playback playback playback Description Press W (S) to increase the number of images Display more images W (S) displayed. To always use the same color lettering, select Manual and choose Dark on light (w;... Ladning anbefales ikke ved temperaturer under 5 eller høyere enn 45 grader Celsius. E button Main command dial Control panel Activate or cancel bracketing/ select number of shots in bracketing sequence (mode P, S, A, or M; 0 133). Page 33 The Camera Body (Continued) P button .....18 Viewfinder eyepiece.....33 Changing settings in the information display Rubber eyecup .....60 .....12 O/Q button Changing settings during live view/movie Delete .....40, 197 recording.....157, 164 Formatting memory cards .....32 Retouching pictures ..... Connections Installing ViewNX 2 Install the supplied software to display and ViewNX 2 edit photographs and movies that have been copied to your computer. Adjust printing options. Please read this Agreement carefully before beginning download. Press the a button. Display picture full frame and Highlight an option and Create retouched copy. If the problem persists, turn the camera off. Shooting with Special Effects To view the currently selected special effect mode, rotate the mode dial to q and press the R button. YOU MAY NOT ALTER OR REMOVE ANY COPYRIGHT, TRADEMARK OR OTHER PROTECTIVE NOTICES CONTAINED IN THE MANUAL. Option Description O Size priority Images are compressed to produce relatively uniform file size. M/Y button Flash mode Flash compensation D button AF-mode button Bracketing Autofocus mode AF-area mode Sub-command dial Mode dial E button Exposure compensation... In other modes, the shutter-release is disabled. Page 51 The AC Wall Adapter Depending on the country or region of purchase, an AC wall adapter may also be supplied with the charger. other indoor scenes. Cards with class 6 or faster write speeds are recommended for movie recording. To use the adapter, insert it into the charger AC inlet (q). RGB histograms, highlights, and overview data are only displayed if corresponding option is selected for Playback display options (0 219). Selecting 1.3× (18×12), however, reduces the angle of view and increases the apparent focal length of the lens. Select Remote control mode (ML-L3). Page 240 Display printing options. e AF-area mode The current AF-area mode. d2: Viewfinder Grid Display G button A Custom Settings menu Choose On to display on-demand grid lines in the viewfinder (0 9) for reference when composing photographs using the DX- format image area (0 63). Page 125 Check the results. Select Choose tab. Frame the opening shot and focus as described in Steps 3 and 4 on pages 153 (for more information on focusing in movie live view, see page 155). The Command Dials The main- and sub-command dials are used alone or in combination with other controls to adjust a variety of settings. Selv om det er flere faktorer som påvirker bildekvaliteten, kan man stort sett si at jo flere megapiksler, desto bedre bilderesultat. Focus: press halfway Shoot: press all the way down The Standby Timer The viewfinder and the control panel shutter speed and aperture displays will turn off if no operations are performed for about 6 seconds, reducing the drain on the battery. Select L (Preset manual) for White balance in the shooting menu. To use live view when the camera is connected to an HDMI-CEC device, select Off for HDMI >... Continuous Release G button A Custom Settings menu The maximum number of shots that can be taken in a single burst in continuous mode can be set to any value between 1 and 100. Playback Menu Defaults Option Default Option Default Playback folder D7100 Slide show Image review Still images and Image type movies After delete Show next... Color Outline G button N retouch menu Create an outline copy of a photograph to use as a base for painting. Focusing in Live View Focus-mode selector To focus using autofocus, rotate the focus-mode selector to AF and follow the steps below to choose autofocus and AF-area modes. By default, new Picture Controls are named by adding a two-digit number Name area (assigned automatically) to the name of the existing Picture Control; to use the default name, proceed to Step 7. In-focus indicator View the photograph (0 39). Basic Setup A language-selection dialog will be displayed the first time the camera is turned on. Table of Contents Q&A Index ..... In the event a dispute arises under or in connection with this Agreement, you hereby consent to personal jurisdiction of Japan and waive any objection that such forum is inconvenient. Sharing Custom Picture Controls Custom Picture Controls created using the Picture Control Utility available with ViewNX 2 or optional software such as Capture NX 2 can be copied to a memory card and loaded into the camera, or custom Picture Controls created with the camera can be copied to the memory card to be used in other D7100 cameras and software and then deleted when no longer needed. THIS DISCLAIMER CONSTITUTES AN ESSENTIAL PART OF THIS AGREEMENT AND NO USE OF THE MANUAL IS AUTHORIZED EXCEPT UNDER THIS DISCLAIMER. AF tuning is not recommended in most situations and may interfere with normal focus; use only when required. Focus the viewfinder. You further consent to service of process in any action arising from this Agreement by regular mail or other commercially reasonable means of receipted delivery. Shooting Mode Role assigned to J button Option... Photographs can not be taken until you have set the time and date. The sensor can be cleaned at any time using the Clean now option, or cleaning can be performed automatically when the camera is turned on or off. JPG... The built-in flash turns a tripod is recommended to prevent off; use of a tripod is recommended to blur; the flash can also be used (0 119). 222 Slide Show..... Index Symbols U (Flexible program) ....48 Assign MB-D15 4 button..259 R (Info) button..10, 12, 159, 166 Assign preview button..255, 260 i (Auto mode)..... For Your Safety To prevent damage to your Nikon product or injury to yourself or to others, read the following safety precautions in their entirety before using this equipment. Do not remove memory cards from the camera, turn the camera off, or remove or disconnect the power source during formatting or while data are being recorded, deleted, or copied to a computer. La det tørke og sett inn nye batterier. G button Tabs Choose from the following menus: • : Playback (0 217) • : Setup (0 261) •... Page 31 The Camera Body (Continued) Built-in flash .....119 Cover for accessory terminal and headphone Mirror ..... i Miniature Effect Press the a button. Press J to start playback. The Playback Menu The Delete option in the playback menu contains the following options. 89, 95 ISO sensitivity step value...234 Monitor brightness.....262 Press the shutter-release button i-TTL.....119, 122, 247 Monitor off delay.....238 all the way down .... AMA15291 Printed in Europe SB3C02(11) 6MB17811-02... NIKON D7100 F5 . Press 1 or 3 to highlight a menu item. Rotate the mode dial to the desired mode. h Mode To view the currently selected scene, rotate the mode dial to h and press the R button. If shooting ends before the specified number of exposures have been taken, a multiple exposure will be created from the exposures that have been recorded to that point. This allows the multi selector to be used to select the focus point. Press J to display PictBridge printing options. Highlight Select image(s) and press 2. Check that the display in the viewfinder is in focus before framing pictures in the viewfinder. 4 Save selected frame Save a selected frame as a JPEG still. Page 144 Choose the HDR strength. Observe due caution when removing memory cards from the camera. Item Description The current battery level expressed as a percentage. Modifications to exposure are added to those made with exposure compensation (0 86), making it possible to achieve exposure compensation values of more than 5 EV. Save user settings. horizon MY MENU Pressing the Fn button displays “MY MENU”... Image Sensor Cleaning If you suspect that dirt or dust on the image sensor is appearing in photographs, you can clean the sensor using the Clean image sensor option in the setup menu. G button Choose movie options. ii Quick Start Guide.....iv Menu Options .....vi For Your Safety .....xxi Notices.....xxiii Introduction Overview.....1 Getting to Know the Camera.....2 The Camera Body .....2 The Mode Dial.....6 The Release Mode Dial .....7 The Control Panel.....8 The Viewfinder.....9 The Information Display..... Image Quality and Size Together, image quality and size determine how much space each photograph occupies on the memory card. Note that protected images will be deleted when the memory card is formatted (0 32, 262). Note that if the MB-D15 is powered by an optional EH-5b AC adapter and EP-5B power connector, the AC adapter will be used regardless of the option selected. If you chose Print select or Print (DPOF) in Step 2, press 4 or 2 to scroll through the pictures on the memory card; to view images in other locations, hold the D button, press 1, and select the desired card and folder as described on page 186. Press the shutter-release button halfway to focus. The Mode Dial Mode dial The camera offers the modes listed below. Page 327 The Built-in Flash The built-in flash can be used with CPU lenses with focal lengths of 16–300 mm, although in some cases the flash may be unable to entirely light the subject at some ranges or focal lengths due to shadows cast by the lens, while lenses that block the subject’s view of the red-eye reduction lamp may interfere with red-eye reduction. 119 Flash Mode .....120 Flash Compensation.....124 FV Lock.....125 Remote Control Photography Using an Optional ML-L3 Remote Control .....127 Wireless Remote Controllers ..... Fine-Tuning White Balance White balance can be “fine-tuned” to compensate for variations in the color of the light source or to introduce a deliberate color cast into an image. Quick Start Guide Follow these steps for a quick start with the D7100. Note that formatting permanently deletes all pictures and other data on the card in the selected slot. Manuals for Nikon products/ 2018/02/15/ Ver.2.0.0 Page 1 DIGITAL CAMERA User's Manual... This Agreement sets forth the entire agreement and understanding between you and Nikon, and supersedes and replaces any other agreements relating to the subject matter of this Agreement. Highlight Non-CPU lens data in the setup menu and press 2. The following operations can be performed while zoom is in effect: Description Press X (T) to zoom in to maximum of approximately 38×... • Battery Charger MH-25 (0 22): Recharge EN-EL15 batteries. In My Menu (O), highlight Rank items and press 2. Custom Picture Controls can be saved to a memory card for sharing among other cameras of the same model and compatible software (0 112). The copy will not be saved if there is insufficient space available on the memory card. Select a photograph. Page 121 White Balance Fine-Tuning The colors on the fine-tuning axes are relative, not absolute. Page 170 Select a mode. Option Description B 51 points Choose from the 51 focus points shown at right. Color Temperature Fine-Tuning When Choose color temp. Pressing the D button, rotate the main command dial to choose the number of shots in the bracketing sequence. Can I overlay two NEF (RAW) photos to make a single image? The items currently displayed in My Menu are indicated by a check mark. The options available are the same as for Assign Fn button (0 259). Page 282 Option Description If DX (24×16) is selected for Image area (0 63), the Fn button can be used Viewfinder grid display to display or hide the framing grid in the viewfinder (0 239). Selecting Folders by Folder Number Select folder by number. Bruk aldri bare hender til å gjøre dette. Choose from the 11 focus points shown at right. Rotate the live view selector to C (live view photography). 209 Saving camera settings....268 Time zone .....265 Scene mode .....41 Time zone and date..... A: Aperture-Priority Auto In aperture-priority auto, you choose the aperture while the camera automatically selects the shutter speed that will produce the optimal exposure. Highlight the following options and press 2 to toggle the highlighted option on or off (to complete the print order without including this information, proceed to Step 5). Page 335 Notes on Optional Flash Units Refer to the Speedlight manual for detailed instructions. Release mode dial Mode Description One photograph is taken each time the shutter- Single frame release button is pressed. Under no circumstances should you touch or wipe the sensor. Please note that the manual and the contact information therein are subject to change without notice. To choose the difference in exposure between the two shots (HDR strength), highlight HDR strength and press 2. Displayed in red if level is too 164, r Sound level high;... Be sure to use the latest Your Imaging Toolbox version of ViewNX 2, which is available for download from the websites listed on page... While the exposure meters are on, rotate the main command dial to choose a shutter speed, and the sub-command dial to set aperture. From a distance of 5 m (16 ft) or less, aim the transmitter on the ML-L3 at either of the infrared receivers on the camera (0 3, 5) and press the ML-L3 shutter-release button. Choose the number of shots. Image Area Regardless of the option selected for Image area in the shooting menu (0 63), all movies and photographs recorded in movie live view (0 161) have an aspect ratio of 16 : 9. Press the release mode dial lock release and turn the release mode dial to E. Creating a Multiple Exposure Multiple exposures can not be recorded in live view. Focus Point Selection The camera offers a choice of 51 focus points that can be used to compose photographs with the main subject positioned almost anywhere in the frame. The cable must have a HDMI mini connector (Type C) for connection to the camera. Page 102 AF-area mode can be selected by pressing the AF-mode button and rotating the sub- command dial until the desired setting is displayed in the viewfinder or control panel. About 2 hours and 35 minutes are required to fully recharge the battery when no charge remains. Bracketing (P, S, A, and M Modes Only) Bracketing automatically varies exposure, flash level, Active D-Lighting (ADL), or white balance slightly with each shot, “bracketing” the current value. If any provision of the Agreement shall be determined invalid for any reason, the remaining provisions shall not be invalidated and shall remain in full force and effect. Focus Lock Focus lock can be used to change the composition after focusing, making it possible to focus on a subject that will not be in a focus point in the final composition. The mirror will be raised and the view through the lens will be displayed in the camera monitor as it would appear in the actual movie, modified for the effects of exposure. Measure white balance. Highlight Image area in the shooting menu (0 224) and press 2. Do not use alcohol, thinner, or other volatile chemicals. “Point-and-Shoot” Photography (i and j Modes) This section describes how to take photographs in i and j modes, an automatic “point-and-shoot” mode in which the majority of settings are controlled by the camera in response to shooting conditions. Taking Photographs Shooting Modes and Framing Options Is there a quick and easy way to take snapshots (i mode)? TO THE MAXIMUM EXTENT PERMITTED UNDER APPLICABLE LAW, NEITHER NIKON, NOR ITS EMPLOYEES, DISTRIBUTORS, DEALERS OR AGENTS SHALL BE LIABLE TO YOU FOR ANY INDIRECT, CONSEQUENTIAL OR INCIDENTAL DAMAGES, LOSSES OR, EXPENSES OF ANY KIND, WHETHER LOSS OF PROFITS, BUSINESS INTERRUPTION, OR OTHERWISE ARISING OUT OF OR RESULTING FROM THE MANUAL, HOWEVER CAUSED, EVEN IF NIKON, ITS EMPLOYEES, DISTRIBUTORS, DEALERS OR AGENTS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, LOSSES, OR EXPENSES. Dirt that can not be removed with a blower can only be removed by Nikon-authorized service personnel. Non-CPU lenses can be used only in A and M modes (0 47); aperture can be adjusted using the lens aperture ring. In center-weighted metering, exposure will be locked at the value metered in a 8-mm circle in the center of the viewfinder. Choose a shorter standby timer delay for longer battery life. For example, moving the cursor to B (blue) when a “warm” setting such as J (incandescent) is selected for white balance will make photographs slightly “colder” but will not actually make them blue. Recommended for snapshots and in other situations in which there is little time to adjust camera settings. Before installing ViewNX 2, confirm that your computer meets the system requirements on page 202. AI 50–300mm f/4.5, modified AI 50– 300mm f/4.5, AI 50–300mm f/4.5 ED, and AI-S 50–300mm f/4.5 ED lenses must be used at a... a button Adjust options. 7, 57 Continuous shooting speed..... Press 1 or 3 to view information about current photograph View photo information (0 187). Attach a Lens The lens generally used in this manual for illustrative purposes is an AF-S DX NIKKOR 18-105mm f/3.5-5.6G ED VR. G button The setup menu contains the following options: Option Option Format memory card Image comment Save user settings Copyright information Reset user settings Save/load settings Monitor brightness... AF-mode button Main command dial AF-A AF-S AF-C Getting Good Results with Autofocus Autofocus does not perform well under the conditions listed below. For information on two-button resets, see page 131. Nikon does not accept liability for any damages or disputes arising from the use of the Copyright information option. Play the movie back as described on page 171; your approximate position in the movie can be ascertained from the movie progress bar. Select i or j Mode. Use this option to share settings among D7100 cameras. Highlight a photograph (to view the highlighted photograph full frame, press and hold the X (T) button;... Hvis du finner en feil i våre ofte stilte spørsmål, vennligst gi oss beskjed ved å benytte vårt kontaktskjema. Page 154 Recompose the photograph. Pressing the D button, rotate the sub-command dial to choose from increments of 1 (5 mired; 0 93), 2 (10 mired), or 3 (15 mired). We may be unable to respond to inquiries from individuals who have not purchased our products. Adjusting Shutter Speed and Aperture While exposure lock is in effect, the following settings can be adjusted without altering the metered value for exposure:... FreeType License (FreeType2) Portions of this software are copyright © 2013 The FreeType Project (“www.freetype.org”). 130 WR-1 Wireless Remote Controllers.....130 WR-R10/WR-T10 Wireless Remote Controllers.....130 Other Shooting Options Two-Button Reset: Restoring Default Settings..... Artist and Copyright fields are blank before lending or transferring the camera to another person. Highlight Choose start/end point and press The dialog shown at right will be displayed; choose whether the current frame will be the starting or end point of the copy and press J. Camera meters a wide area of the frame and set exposure according to tone distribution, color, composition, and, with type G or D lenses (0 296), distance information (3D color matrix metering II;... Effekten forsterkes i mørke omgivelser. The Viewfinder 11 12 1516 17 18 19 Monochrome indicator (displayed in % mode or ISO sensitivity indicator .....79 when the Monochrome Picture Control or a “K” (appears when memory remains for over Picture Control based on Monochrome is 1000 exposures) .....35 selected) .....105 Flash-ready indicator.....38, 241 Special effects mode indicator.....177... Press 2 to continue. Nikon retain ownership of the Manual and all copies thereof and all related intellectual property rights, and reserves all rights not expressly granted to you under this Agreement. Page 13 N RETOUCH MENU (0 273) O MY MENU (0 291) D-Lighting Add items – Playback menu Red-eye – Shooting menu correction Custom setting menu Trim – Setup menu Monochrome Black-and-white Retouch menu Remove items Sepia – Rank items Cyanotype – Filter effects Choose tab Skylight... For more information on white balance, see page 89. Page 160 Option Default Autofocus (live view/movie) Autofocus mode AF-S AF-area mode m, r, w, %, g, u, 1, 2, 3, P, S, A, M Wide-area AF n, 0 Normal-area AF i, j, k, l, p, o, s, t, u, v, x, y, z Face-priority AF Focus point Center... Manual Focus Manual focus is available for lenses that do not support autofocus (non-AF NIKKOR lenses) or when the autofocus does not produce the desired results (0 72). Option Description • On: Turn AF tuning on. Det var nyttig (211) Les mer Den beste måten å lagre et litiumionbatteri er ved en temperatur mellom 5 og 45 grader Celsius. Page 139 Name the Picture Control. The headings of the sections of this Agreement are inserted for convenience only and shall not constitute a part hereof or affect in any way the meaning or interpretation of this Agreement. While the exposure meters are on, rotate the main command dial to choose a shutter speed of Bulb (A) or Time (%). Using the P Button The options listed below can be accessed by pressing the P button before recording begins in movie live view (pressing the P button while recording is in progress has no effect). 1.5× that of lenses with FX format angle of view Effective pixels 24.1 million... Page 374 HDMI Licensing LLC. Attach a lens (0 26). R button Release mode ..... q mode Main command dial Monitor Image Quality and Size Set image quality (0 66). In delayed remote mode, the self-timer lamp will light for about two seconds before the shutter is released. Select Manage Picture Control in the shooting menu. Page 334 Other Flash Units The following flash units can be used in non-TTL auto and manual modes. Release Mode Regardless of the release mode selected, the camera will take the specified number of shots at each interval. Autoexposure Lock Use autoexposure lock to recompose photographs after using center-weighted metering and spot metering to meter exposure. Live view may also end automatically to prevent damage to the camera’s internal circuits;... The control panel turns off briefly while settings are reset. At the time of writing, the following accessories were available for the D7100. Page 324 11 Range of rotation for AI 80–200mm f/2.8 ED tripod mount is limited by camera body. If the camera was able to measure a value for white balance, C will flash in the control panel for about six seconds, while the viewfinder will show a flashing Control panel Viewfinder If lighting is too dark or too bright, the camera may be unable to measure white balance. Package Contents Confirm that the package contains the following items: BS-1 accessory shoe cover DK-23 rubber eyecup D7100 camera BF-1B body cap EN-EL15 rechargeable MH-25 battery charger (AC DK-5 eyepiece cap (0 60) Li-ion battery (with terminal wall adapter supplied only in cover) countries or regions where required. Select white balance bracketing. selected for playback. Page 370 Nikon reserves the right to change the specifications of the hardware and software described in this manual at any time and without prior notice. • On: Gain is adjusted according to number of exposures actually recorded (gain for each exposure is set to for 2 exposures, for 3 exposures, etc.). Choose WB bracketing for Custom Setting e6 Auto bracketing set. If the Fn button is pressed when the command dials are rotated, changes 1 step spd/ to shutter speed (modes S and M) and aperture (modes A and M) are made in increments of 1 EV, regardless of the option selected for Custom Setting... 36 P button .....18 Assign shutter button....260 j (Auto (flash off) mode) ... Formatting Memory Cards Formatting memory cards permanently deletes any data they may contain. Image Size Image size is measured in pixels. Page 129 Choosing a Source Image To view the image highlighted in Step 4 full frame, press and hold the X (T) button. The P button Use the P button for quick access to a variety of functions during viewfinder and live view photography, movie recording, and playback. Adjust settings for group A. Select mirror up mode. A L appears next to selected items; to deselect, highlight and press 2. Page 110 When On is selected, the viewfinder and control panel show ISO-AUTO. Shutter-release Lock exposure. • Rechargeable Li-ion Battery EN-EL15 (0 22, 24): Additional EN-EL15 batteries are available from local retailers and Nikon-authorized service representatives. Følgende kan gjøres for å unngå det: Ikke la de som fotograferes se rett inn i kameraet, sørg for bedre belysning, ta bildet nærmere motivet og/eller ikke zoom inn for mye. The area that will be in focus in the copy is indicated by a yellow frame. The Flash Sync Mode Display M does not appear in the control panel flash sync mode display when – – is selected for Built- in flash > Mode. Items indicated by a V icon can not be selected. Page 124 Select a preset. Delete all pictures in the folder currently selected for R All playback (0 217). Creative Photography (Scene Modes) The camera offers a choice of “scene” modes. Med eldre batterier var dette tilfelle. translated into any language in any form, •... Before After Press 1 or 3 to choose the amount of correction performed. Protected presets can not be modified and the Fine-tune and Edit comment options can not be used. Flash Photography Using the Built-in Flash The built-in flash has a Guide Number (GN) 12/39 (m/ft, ISO 100, 20 °C/68 °F) and provides coverage for the angle of view of a 16 mm lens. press J. While bracketing is in effect, a bracketing progress indicator will be displayed in the control panel. Saving User Settings Mode dial Select a mode. Trim G button N retouch menu Create a cropped copy of the selected photograph. Printing Multiple Pictures Display the PictBridge menu. Highlight Active D-Lighting in the shooting menu and press 2. Press + Command Dials Selecting Press + command dials displays the following options: Option Description Choose Press the Fn button and rotate a command dial to choose an image area image area (0 63). How do I make JPEG copies of RAW (NEF) photos? Night Vision Use under conditions of darkness to record monochrome images at high ISO sensitivities (with some noise in the form of randomly-spaced bright pixels, fog, or lines). Highlight Auto gain and press 2. Editing Movies Trim footage to create edited copies of movies or save selected frames as JPEG stills. Multiple exposures produce colors noticeably superior to those in software-generated photographic overlays created from existing images. The Image Area Menu Select Image area in the shooting menu. Highlight Select folder from list and press 2. Page 95 The following options can be accessed from the shooting menu. The Manual is protected by Japanese copyright law and international copyright laws and treaties. • The shutter-release button can not be used to focus when AF-ON is assigned as the Press option for Custom Setting f2 (Assign Fn button, 0 253), f3 (Assign preview button, 0 255), f4 (Assign AE-L/AF-L button, 0 256), or f9 (Assign MB-D15 4 button, 0 259). Continuous Release.....240 d7: File Number Sequence .....240 d8: Information Display .....241 d9: LCD Illumination .....241 d10: Exposure Delay Mode.....241 d11: Flash Warning.....241 d12: MB-D15 Battery Type .....242... One EN-EL15 battery (camera): Approximately 950 shots One EN-EL15 battery (MB-D15): Approximately 950 shots Six AA alkaline batteries (MB-D15): Approximately 450 shots • Photographs, continuous release mode (Nikon standard One EN-EL15 battery (camera): Approximately 3550 shots One EN-EL15 battery (MB-D15): Approximately 3550 shots Six AA alkaline batteries (MB-D15): Approximately 1200 shots •... The built-in flash and AF-assist illuminator turn off; use of a tripod is recommended to prevent blur when lighting is poor. Before formatting, be sure to make backup copies as required. Selecting this option displays a list of dates. Larger, higher quality images can be printed at larger sizes but also require more memory, meaning that fewer such images can be stored on the memory card (0 348). • Check that contacts are — clean. If the product will not be used for an extended period, remove the battery to prevent leakage and store the camera in a plastic bag containing a desiccant. Press J to display selective color options. These Download Terms and Conditions ("Agreement") constitute a legal agreement between you (either an individual or single entity) and Nikon Corporation or its associated company ("Nikon") setting forth the terms and conditions governing your download of the operation manual for our products (“Manual”). ... Nikon D7100 user manual | Read it for free or download the Nikon D7100 user manual in PDF Format Trenger du en bruksanvisning for Nikon D7100 Digitalkamera? 1 Under Import pictures and videos, click Change program. Page 326 Lens f-number The f-number given in lens names is the maximum aperture of the lens. Press J to copy the photograph. Page 157 Exiting Remote Control Mode Remote control is cancelled automatically if no photograph is taken before the time selected for Custom Setting c5 (Remote on duration (ML-L3), 0 238), Off is selected for Remote control mode (ML-L3), a two-button reset is performed, or shooting options are reset using Reset shooting menu. If the desired frame is not currently displayed, press 4 or 2 to advance or rewind (to skip to 10 s ahead or back, rotate the main command dial;... Select the highlighted folder. Live view selector Press the a button. Choosing a Focus Mode The following autofocus modes are available in live view (note that full-time-servo AF is not available in g and i modes): Mode Description... Option Description Q Selected Delete selected pictures. Ethernet and Wireless Networks The optional UT-1 communication unit (0 310) requires Wireless Transmitter Utility version 1.4.0 or later (the Wireless Transmitter Utility is supplied with the UT-1; the latest versions of the UT-1 firmware and Wireless Transmitter Utility can be downloaded from the websites listed on page xxvi). To choose a mode, press the mode dial lock release and rotate the mode dial. Selecting a Picture Control The camera offers a choice of preset Picture Controls. Release Mode Choosing a Release Mode To choose a release mode, press the release mode dial lock release and turn the release mode dial to the desired setting. The Live View Display: Live View Photography Item Description The amount of time remaining before live view ends q Time remaining automatically. Page 200 The 2 Icon 2 is displayed in full-frame and movie playback if the movie was recorded without sound. If the focal length of the lens is known: • Power zoom can be used with optional SB-910, SB-900, SB-800, SB-700, and SB-600 flash units •...